



Features & Benefits

- Daisy chain power (up to 7 fixtures / circuit)
- Daisy chain controls (up to 50 fixtures / circuit)
- IP67 Rating – suitable for wet environment
- Secure M19 twist-lock power connections
- Long, slim LED array provides great light coverage with minimum blockage of natural light
- Quality components including Osram LED
- 1-10V dimming capable (Dim to 100%)
- 1,600 μmol at 500W (3.2 $\mu\text{mol}/\text{W}$)
- Quick install
- Long life – 50,000 hours (L90)
- Red/Blue spectrum, ideal for greenhouse supplement
- Secure 3' hanging chains (143 lb working load)

Output

- PPF (μmol) 1,600
- Efficacy ($\mu\text{mol}/\text{J}$) 3.2
- Spectrum Red/Blue supplemental spectrum



Electrical

Input power (W) 500
 Input voltage (V) AC120-277 auto sense


AC Voltage (V)	120	240	277
AC Current (A)	4.36	2.17	1.91
Power Factor	0.99	0.98	0.96
Max fixtures / 20A	3	6	7

Dimming 1-10V

Mechanical & Safety

Weight (lbs.) 27.9
 Dimensions (LxWxH inches) 47.6 x 4.3 x 8.1
 Input/output power M19 3-pin
 Input/output control M16 2-pin
 Operating temperature ($^{\circ}\text{C}$) -20 to 35

3 Year Warranty



Ordering Codes: Power Cords

PC-14G-6-120	Power cord 6' with NEMA 5-15P 120V plug
PC-14G-6-240	Power cord 6' with NEMA 6-15P 240V plug
PC-14G-6-277	Power cord 6' with NEMA L7-15P 277V plug
PCF-14G-6	Fixture to fixture power cord 6' with M19 plugs
PCF-14G-10	Fixture to fixture power cord 10' with M19 plugs

Ordering Codes: Controls

CC-5-1	Fixture to fixture control cord 5', M16 plugs
CC-10-1	Fixture to fixture control cord 10', M16 plugs
CD-1	Zigbee Control Device
GA-1	Gateway
CD-3	Hard-wired Control Device

